

Series 3900 Double Hung Window

Also Available: 2- and 3-lite sliders and picture windows

- Exclusive InsulKor™ polyurethane fiberglass-enriched sash reinforcement for superior thermal and structural performance
- 3/4" constant force coil balance offers incredibly easy sash mobility
- Fusion-welded sashes and frame add strength and boost insulation
- Low-E glass with insulating argon gas yields outstanding thermal efficiency
- DP 60 rating (window size tested 36" x 74")
- Beveled mainframe offers a stylish exterior appearance
- Dual push-button night latches position sashes for optimal ventilation
- Integrated slim-line lift rail allows you to easily operate sash
- 4-1/4" frame thickness enhances appearance as well as structural integrity
- External accessory groove accommodates nail fin option
- Extruded Full screen* is standard and removable from the inside
- Dual low profile, positive-action cam locks increase security (2 locks standard at 27-1/4" width or wider)
- Full interlocking lock and meeting rail
- Full vinyl sash dam on sill and high-performance weather stripping protect against air infiltration
- 3.25" jamb depth for ideal window sizing
- Transferable, limited lifetime warranty
- Lifetime glass breakage warranty



Featuring
InsulKor™
Technology



Color Options**



†Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

Lock Options**



Custom Options

- Low-E Glass
- Ultra Low-E / Argon Gas (may be required for Energy Star rating)
- Silent Guard® with noise control STC 34 performance
- Triple-pane, R-5 compliant glass panels
- Super Spacer® nXt™ sealant system for optimal thermal performance (standard with triple-pane option)
- InsulKor™ multi-cavity foam-filled frame injections
- Exclusive locking half screen*
- 5/8" or 3/4" flat, 5/8" or 1" contoured grid; historical, traditional or modern patterns available
- 1-1/8" simulated divided lite (SDL) grid and architectural shapes
- Nail fin accessory for use in remodeling or new construction applications
- Obscure or double-strength glass
- Decorative glass

*Screens are not meant to restrain a child from falling through an open window.

**Printing process may affect color shown. Please refer to actual window sample when selecting colors.

Manufacturer reserves the right to substitute components as necessary for continued product improvement. WL-3900-1/15